



North American Headquarters
 7966 NC 56 Hwy Louisburg, NC 27549
 919.497.0010
www.palzivna.com

Certificate of Compliance

Standard for Approval	MS-AY-512 Type 2
Product Description	Vizion V3.0 (3.0 PCF)

Properties	Data	Standard Requirements	UOM	Status
Average Density	3.02	2.25 - 3.75	lb/ft ³	Pass
Tensile Strength Direction A	76.8	24 (min)	psi	Pass
Tensile Strength Direction B	81.5	35 (min)	psi	Pass
Elongation Direction A	338	52 (min)	%	Pass
Elongation Direction B	305	65 (min)	%	Pass
Compressive Deflection 25%	11.5	10 - 19	psi	Pass
Compression Set	15.7	43 (max)	%	Pass
Thermal Stability Direction A	-1.4	- 5 (max)	%	Pass
Thermal Stability Direction B	-1.6	- 4 (max)	%	Pass
Water Absorption	0.007	0.4 (max)	kg/m ²	Pass
Flammability	34.5	100 (max)	mm/min	Pass

* Direction A Length of bun, Direction B Width of bun

Date of Compliance:	5/21/2015
---------------------	-----------

Palziv North America certifies that this product was inspected and tested in accordance with written standards, and that the results are correct at the time of inspection. Due to the nature of the product, results will vary over time.

Original standard requirements for type 2 roll stock deviates to bun stock, Density from 1.8 - 2.2 deviates to 2.25 - 3.75, and Compressive Deflection from 1.7 - 9.1 deviates to 10 - 19.

Authorized by

A handwritten signature in black ink that reads "Joseph M Andolsen".

Joe Andolsen
 Quality Manager
 Palziv North America