

North American Headquarters 7966 NC 56 Hwy Louisburg, NC 27549 919.497.0010 www.palzivna.com

Certificate of Compliance				
Standard for Approval		MS-AY-512 Type 1		
Product Description		Vizion V2.0 STD (2.0 PCF)		
Descrition	Data	Standard		01-1-1-1
Properties	Data	Requirements	UOM	Status
Average Density	2.10	1.4 - 2.6	lb/ft ³	Pass
Tensile Strength	59.1	19 (min)	PSI	Pass
Elongation (% to break)	286	89 (min)	%	Pass
Compressive Deflection 25%	8	2.9 - 9.0	PSI	Pass
Compression Set	24	32 (max)	%	Pass
Thermal Stability	-1.9	- 7 (max)	%	Pass
Flammability (tested at				Pass (≥ 0.25"
11.6mm)	63	100 (max)	mm/min	thickness)
Water Absorption	0.0312	0.2 (max)	kg/m²	Pass
Date of Compliance:	4/12/2017]		

Palziv North America certifies that this product was inspected and tested in accordance with written standards, and that the results are correct at the time of inspection. Due to the nature of the product, results will vary over time.

Authorized by

Joseph M andolsen

Joe Andolsen **Testing Manager** Palziv North America