



North American Headquarters
 7966 NC 56 Hwy Louisburg, NC 27549
 919.497.0010
www.palzivna.com

Certificate of Compliance

Standard for Approval		MS-AY-551 Grade 10 (MS.90109_Rev. C)		
Product Description		Vizion V4.0 (4.0 PCF)		
Properties/Procedure	Data	Standard Requirements	UOM	Status
Density- ASTM D3575 Suffix W	61	45-70	kg/m ³	Pass
Tensile Strength- ASTM D3575 Suffix T	741	450 (min)	kPa	Pass
Elongation at Break- ASTM D3575 Suffix T	302	110 (min)	%	Pass
Compression Set- ASTM D3575 Suffix B	7	30 (max)	%	Pass
Tear Strength- ASTM D3575 Suffix G	3.8	2.5 (min)	kN/m	Pass
Load Deflection 25%- ASTM D3575 Suffix D	133	135-175	kPa	Dev. Req.
Stain Resistance- ASTM D925 Method A	No Staining	No Staining	-	Pass
Water Absorption- ASTM D3575 Suffix L	0.029	0.5 (max)	kg/m ²	Pass
Dimensional Stability- ASTM D3575 Suffix S (3 hrs. 100°C)	3.6	10	%	Pass
Flammability- FMVSS302 (tested at 11.2mm)	29	100 (max)	mm/min	Pass (≥ 0.25" thickness)
Date of Compliance:		20-Mar-18		

Palziv North America certifies that this product was inspected and tested in accordance with written standards, and that the results are correct at the time of inspection. Due to the nature of the product, results will vary over time.

Authorized by

Joe Andolsen
 Testing Manager
 Palziv North America