



North American Headquarters
 7966 NC 56 Hwy Louisburg, NC 27549
 919.497.0010
www.palzivna.com

Certificate of Compliance

Standard for Approval	WSS-M99P48-A3
Product Description	Vizion V6.0 STD 2-step (6.0 PCF)

Properties	Result	Standard	UOM	Status
3.2.1 Odor Variant A Condition 1	1*	3 (max)	-	Pass
Variant A Condition 2	1.5*			Pass
Variant A Condition 3	2*			Pass
3.2.2 Fogging	93**	70 (min)	-	Pass
3.2.3 Flammability	24	100 (max)	mm/min	Pass
3.2.4 Resistance to Mildew	Pass	No Mildew	-	Pass
3.2.5 Stress Cracking Test	N/A***	No Cracking/Crazing	-	N/A
3.2.6 Accelerated Weathering Resistance	N/A****	4 (min)	-	N/A
3.2.7 Corrosion	No Galvanic Corrosion**	No Galvanic Corrosion	-	Pass
3.3.1 Tensile Test	1.12	Report Value	MPa	Report Value
3.3.2 Density	6 (nominal)	Report Value	lb/ft ³	Report Value
3.3.3 Tear Resistance Test	6232	Report Value	N/mm	Report Value
3.3.4 Constant Deflection Compression Set Test	9.87	Report Value	%	Report Value
3.3.4.2 Steam Autoclave Aging Exposure	N/A*****	+/- 40% max from original value	%	N/A
3.3.4.2 Dry Heat Aging Exposure	N/A*****	+/- 10% max from original value	%	N/A

Date of Compliance:	1-Dec-15
---------------------	----------

Palziv North America certifies that this product was inspected and tested in accordance with written standards, and that the results are correct at the time of inspection. Due to the nature of the product, results will vary over time.

*Results from V4.0 STD. V6.0 STD presumed to pass based on these results

** Results from V2.0 STD. V6.0 STD presumed to pass based on these results.

*** No plasticizers, mineral oil, or solvents.

****Not applicable for interior parts.

*****Not applicable for x-linked PE Foam

Authorized by

Joe Andolsen
 Quality Manager
 Palziv North America