



North American Headquarters  
 7966 NC 56 Hwy Louisburg, NC 27549  
 919.497.0010  
[www.palzivna.com](http://www.palzivna.com)

## Certificate of Compliance

Standard for Approval		GMW15063- Type 10		
PNA Product Description		F4.0 MDR/FR-H2		
Specification/Method	Results	Specified Value	Unit	Status
Fogging/VOCs- GMW3235 Method B-Y1-T1	0.1	≤ 4	mg	Meets
Flammability (as is)- GMW3232	0	< 100	mm/min	Meets
Flammability (aged)- GMW3232	0	< 100	mm/min	Meets
Interior Emissions- GMW15634	6	VOC ≤ 600	µg/g	Meets
Interior Emissions- GMW15634	24	SVOC ≤ 1000	µg/g	Meets
Resistance to Odor Wet Condition (Code A)- GMW3205	7.25	≥ 6	-	Meets
Resistance to Odor Dry Condition (Code B)- GMW3205	7.25	≥ 6	-	Meets
Mildew- GMW3259	N/A	No Mildew	-	N/A
Thickness- ISO 1923	6.3	Report	mm	Report
Dimensional Stability GMW4217	0.03	2 +/- 0.5	%	Meets
Density- ISO 845	66.7	70 +/- 10	kg/m <sup>3</sup>	Meets
Compression Load Deflection 10% Deformation- ISO 844	53.9	> 25	kPa	Meets
Compression Load Deflection 25% Deformation- ISO 844	83.7	Report	kPa	Report
Compression Load Deflection 50%- ISO 844	165	Report	kPa	Report
Tensile Strength- ISO 1926	521	Report	kPa	Report
Elongation at Break- ISO 1926	136	Report	%	Report
Comp Set 50%, 1/2hr- ISO 1856- B	34.4	Report	%	Report
Comp Set 50%, 24hr- ISO 1856- B	19.6	Report	%	Report
Date of Compliance:	22-Jan-16			

Palziv North America certifies that this product was inspected and tested in accordance with written standards, and that the results are correct at the time of inspection. Due to the nature of the product, results will vary over time.

Authorized by

Joe Andolsen  
 Testing Manager  
 Palziv North America