




## Industry Compliance Vizion

Palziv North America  
7966 NC 56Hwy Louisburg, NC 27549  
919-497-0010

Standard for Approval	DBL 5455 (PVR 23)
Product Description	Vizion 3pcf STD

Properties	PNA Data	Standard Requirements	UOM	Status
Nominal Density	48	45 - 64.9	Kg/m <sup>3</sup>	Pass
Tensile Strength	Min. 450	Min. 300	kPa	Pass
Elongation	Min. 280	Min 100	%	Pass
Fogging	4.7	250	kN/m	Pass
Compression Deflection 25%	Min. 60	Min 50	kPa	Pass
Odour	5.8 *	3		See remark
100C for 24h	N/A	2	%	N/A
Flammability	OK	100	mm/min	Pass - 6mm and up
Cold bending at -40C	OK	No cracks		Pass

\* GMW3205 - 1 to 10

Date of Compliance	04/16/2015	QA Manager	 Gil Cimering Palziv <a href="mailto:gcimering@palziv.com">gcimering@palziv.com</a>	Gil Cimering
--------------------	------------	------------	--	--------------

Data represents typical values tested in accordance with written standards.  
The information above on **Fuzion**® or **Vizion**® chemically cross-linked polyethylene foam is presented to the best of our knowledge.  
Results are measured by testing according to ASTM standards.

QCFV-IC-201