



North American Headquarters
 7966 NC 56 Hwy Louisburg, NC 27549
 919.497.0010
www.palzivna.com

Certificate of Compliance

| | |
|-----------------------|-----------------------|
| Standard for Approval | NAPS-M5356-028-01 |
| Product Description | Vizion V4.0 STD/FR-H1 |

| Physical Properties | Data | Standard Requirements | UOM | Status |
|------------------------------------|-----------------------|-----------------------|-------------------|----------------|
| Density | 70.5 | 64 +/- 10 | kg/m ³ | Pass |
| Shore OO Hardness | 73.7 | 56 +/- 6 | Shore OO | Not Applicable |
| Compression Set @ 50% 1/2 hr | 28.1 | <40 | % | Pending |
| Compression Set @ 50% 24 hr | 10.7 | <15 | % | Pass |
| Tensile Strength | 606 | >598 | kPa | Pass |
| Elongation | 259 | >425 | % | Not Applicable |
| Tear | 413 | >289 | kg/m | Pass |
| Fogging NES M0161 Type 5 | Not Tested | - | - | Not Applicable |
| FMVSS302 (tested at 3mm thickness) | 72.6, 67.8, SE, SE, 0 | 100 (max) | mm/min | Pass |

| | |
|---------------------|-----------|
| Date of Compliance: | 2/18/2016 |
|---------------------|-----------|

Palziv North America certifies that this product was inspected and tested in accordance with written standards, and that the results are correct at the time of inspection. Due to the nature of the product, results will vary over time.

Authorized by

A handwritten signature in black ink that reads "Joseph M Andolsen".

Joe Andolsen
 Quality Manager
 Palziv North America